



| 2/3" 0.4x (0.346x ~ 0.44x) TELECENTRIC | | | | |
|-----------------------------------------|------------|----------------------------------------|-----------|-----------|
| MAGNIFICATION | | 0.4x | 0.44x | 0.346x |
| N.A.(OBJECT) | | 0.04 | 0.04 | 0.04 |
| ELEMENT | | 9GROUPS 12ELEMENTS | | |
| IMAGE SIZE | | 6.6x8.8mm | 6.6x8.8mm | 6.6x8.8mm |
| SHOOTING RANGE | VERTICAL | 16.5mm | 15.0mm | 19.1mm |
| | HORIZONTAL | 22.0mm | 20.0mm | 25.4mm |
| | DIAMETER | 27.5mm | 25.0mm | 31.8mm |
| DISTORTION (TV) | | -0.009% | 0.01% | 0.02% |
| WORKING DISTANCE | | 112.7mm | 112.7mm | 112.7mm |
| FLANGE BACK | | 17.526mm in air | | |
| FRONT/REAR EFFECTIVE DIA. | | FRONT ϕ 42.2mm REAR ϕ 15.5mm | | |
| MOUNT | | C-MOUNT | | |
| EXIT PUPIL | | 2619.1mm | 116.6mm | -54.6mm |
| TEMPERATURE RANGE | | -10~+50 ° C | | |
| STORAGE TEMPERATURE RANGE | | -20~+60 ° C | | |
| RESOLUTION | | 120lp/mm | | |
| TELECENTRICITY | | 99% | | |
| WEIGHT | | 420g | | |

NOTE:Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



| | | | | | |
|-----------|-------|---------|------------------------------------|----------|--------|
| | | 尺 度 | 1/2 | 工場 番号 | TL1125 |
| | | 機種 名 | 0.4x VARIFOCAL TELECENTRIC LENS | | |
| 2015.4.20 | 更新 | 機種 番 | LM1125TC 外観図 | | |
| 2015.2.9 | 作成年月日 | | | | |