



1" 1.8/6mm C		1"	2/3"	1/1.8"
FOCAL LENGTH		f=6mm		
F-NUMBER		F=1:1.8, 2.8, 4.0, 8.0		
PICTURE SIZE		9.6×12.8mm	6.6×8.8mm	5.4×7.2mm
ANGLE OF VIEW (°)	VER. ANGLE	79.4°	58.0°	48.2°
	HOR. ANGLE	96.8°	74.1°	62.6°
	DIA. ANGLE	108.3°	87.7°	75.5°
DISTORTION (TV)		-0.2%		
FIELD OF VIEW (MINIMUM FOCUS DISTANCE)	VER.	196.3mm	130.9mm	105.9mm
	HOR.	267.4mm	178.7mm	143.7mm
	DIA.	334.1mm	228.0mm	183.1mm
MINIMUM FOCUS DISTANCE		0.1m		
FLANGE BACK		17.526mm in air		
BACK FOCUS		11.1mm in air		
FILTER SCREW SIZE		-----		
FRONT/REAR EFFECTIVE DIA.		FRONT ϕ 46.0mm REAR ϕ 16.8mm		
MOUNT		C-MOUNT		
EXIT PUPIL		-293.3mm		
TEMPERATURE RANGE		-10~+50°C		
STORAGE TEMPERATURE RANGE		-20~+60°C		
RESOLUTION CENTER/CORNER		CENTER 100lp/mm CORNER 80lp/mm		
WEIGHT		180 g		

NOTE: Specifications and availability are subject to change without notice

注) 本仕様については、予告なしに変更する場合があります。

		尺 度	1/1	工場 番号	HR1059SR
		機 種 名	1" F1.8 f=6mm		
		機 種 番	LM6HC-V 外観図		
2025.2.26	作成年月日				